



Pedestal Grade	Stud Size	Base Size	Void Range
Medium/Heavy	1"	100x100mm	26-675mm

Head

The head is a 90mm diameter disc of steel construction welded to an extended 3/4" BSP domed socket . An anti-vibration cap can be supplied suitable for use with or without stringers that has eight integral upstands to ensure that panels are aligned and retained in position while being instantly removable with the correct lifting device. The head is threaded to 3/4" BSP and fitted onto the upstand with a total vertical adjustment of 50mm in order to accommodate sub-floor tolerances.

Threaded Column

The 3/4" threaded hollow tube is electro plated and assembled with a lightweight nut to offer the locking facility.

Base

The base is a steel formed 100mm square with the upstand welded to it. Pre-formed holes are incorporated to facilitate mechanical fixings if required.

Manufacture

Manufactured within the UK, allowing us to offer total flexibility whilst maintaining the highest possible quality standard and ensures fast reaction and a reliable service. Materials used are sourced from high quality suppliers and use renewable, sustainable sources and suppliers wherever possible. We can also offer a bespoke service and specialise in replicating and reproducing existing raised floors.

Floorplan Systems Limited

The Square
Great Eccleston, Preston
Lancashire. PR3 0ZB. United Kingdom

☎: +44 (0)1995 670 110
☎: +44 (0)1995 670 457
✉: enquiries@floorplansystems.co.uk
🌐: www.floorplansystems.co.uk

